



Sports Development Group / Groupe de Développement Sportif

2026 ASN Canada FIA NATIONAL AUTOSLALOM REGULATIONS

Appendix B SCCA

SUPPLEMENTARY CATEGORIES 2026

Published by:

GDS - ASN Canada,

200 circuit Gilles-Villeneuve, Montreal, Quebec, H3C 1A9

Telephone: (514) 350-8203 Email: info@asncanada.ca

**ASN CANADA IS THE GOVERNING BODY OF MOTORSPORT IN CANADA
APPOINTED BY THE FEDERATION INTERNATIONALE DE L'AUTOMOBILE**

These regulations are intended to assist in the conduct of events and to further general safety.

They are a guide, and in no way a guarantee against injury or death to participants, spectators or others.

Canadian territories and regions may adopt these regulations for use within their jurisdictions if they choose to do so including the sole responsibility for the administration thereof.

No express or implied warranties of safety or fitness for a particular purpose shall be intended or result from publication of or compliance with these Regulations.

The contents of this document are copyright may be reproduced only with permission in writing from GDS ASN Canada

Note: Regulations that are changed from the previous edition are indicated by a *red, bold, italics font*.

Go-karts are not allowed in SoloSport competitions.



APPENDIX B - DEVELOPMENTAL/EXHIBITION CATEGORIES

DEVELOPMENTAL CLASSES

Club Spec

Objective

Provide an affordable multipurpose package that combines a street-ready, autocross capable and track appropriate performance in a single car using specified parts.

AUTHORIZED CHANGES/MODIFICATIONS

For most up to date rules go to scca.com/clubspe

- A. If a change or modification is not specifically authorized, it is not allowed. All repairs must comply with factory-authorized methods and procedures, or industry standard methods, as follows: If the manufacturer does not provide an appropriate method of repair, industry standard methods and procedures may be used. Such repairs may not result in a part or combination of parts that provides a performance advantage (e.g., significant change to weight, suspension control, power, etc.) as compared to the standard part(s). Competitors are strongly cautioned to use this allowance to make common-sense repairs only.
- B. Wheel lug studs (e.g., length) and lug nuts may be changed.
- C. Components which are normally expendable and considered replacement parts may be used provided they are essentially identical to the standard parts, used in the same location, and provide no performance benefit. Examples are:
 - a. Clutch and related components (excluding flywheel).
 - b. Hardware (nuts, bolts, clips, etc.)
- D. Parts superseded by the Manufacturer may be used.
- E. These allowances are strictly to permit components to be replaced from alternate sources other than the original manufacturer. They should not be construed as an allowance to replace components with those which could be considered a "higher performance" alternative.
- F. It is not permitted to use non-compliant parts even if they have been set to the manufacturer's specifications.

Bodywork/Interior

- A. Front bumpers, rear bumpers, body trim pieces, and attachment points may be reinforced to prevent or repair damage from hitting cones. Reinforcements that are not visible to the exterior of the car are allowed. Such repairs and/or reinforcements may serve no other purpose.
- B. Accessories, gauges, indicators, lights, and other appearance, comfort-and-convenience modifications which have no effect on performance and/or handling and do not materially reduce the weight of the car are permitted. This does not allow driver's seat substitutions, or the removal of "tow hooks" or "tie-down loops." Data acquisition systems (including video cameras) and the accompanying sensors are allowed but may

Club Spec

serve no other purpose during a run than real-time display and data recording.

C. Alternate Shift knobs are allowed.

D. Spare tires, tools, and jacks may be removed. Any fastening hardware and/or other pieces that can no longer be firmly secured in the absence of the spare tire may be removed if necessary to ensure compliance with Solo® Rules section 3.3.3.B.1, Safety Inspections, Inspection Requirements.

E. Cars may add one (1) rear trailer hitch. Factory tie downs and cosmetic pieces (e.g., diffusers) may be modified or removed to facilitate hitch installation. Complete or partial removal of the hitch is allowed for competition, provided it does not result in a reduction in weight compared to the unmodified standard configuration.

F. Tow bar brackets may be installed and may serve no other purpose.

G. Any item not permanently in place by manufacturer-installed fasteners may be removed (i.e., emergency tool kits).

Safety

A. Provided the vehicle fully meets SCCA Safety Level 2 as defined in the Time Trials Rules, the following may be added, replaced, or modified within the guidelines stated in Safety Level 2:

- Compliant Rollbar (Required for Safety Level 2)
- Fixed back racing seats for driver and passenger side
- Racing harness(es)
- Replacement of steering wheel and/or removal of steering wheel airbag

Suspension

A. Alignment: Both the front and rear suspension may be adjusted through their designed range of adjustment by use of the specified parts. No suspension part may be modified for the purpose of adjustment unless such modification is specifically authorized by the manufacturer service documentation.

B. Bushings:

- Suspension bushings as supplied in the kits are mandatory.
- Those not included in the supplied kits may not be replaced with bushings of a different material or dimension.

Electrical System

A. The make of spark plugs is unrestricted.

B. Tire Pressure Monitoring Systems (TPMS) may be disabled. Altering the signal to the TPMS module is allowed.

Engine and Drivetrain

A. The engine management system parameters and operation of internal combustion engines may be modified only via the methods listed below.

- OE ECU software may be reprogrammed, but no changes to the

Club Spec

factory ECU hardware are permitted.

b. Any OE OBD2 or newer communications port functionality must remain.

B. Oil filters are unrestricted.

C. Lubricants and fluids are unrestricted.

D. Fuel must be Federally approved for use on public highways and widely distributed and typically sold in filling stations, commonly called “pump fuel” with typical octane ratings or AKI (Anti-Knock Index) (R+M/2) displayed on the pump between 87 and 93. The maximum octane rating allowed is what is typically delivered from a pump marked 93 octane*. Fuels comprised of more than 15% ethanol may only be used when specified by the manufacturer (e.g., in the owner’s manual for flex-fuel vehicles).

*Octane verification: Octane levels will vary from the number listed on the pump. Octane testing has a “margin of error” and different testing procedures will produce similar but different results. For the purposes of testing gasoline, a result that exceeds 95.9 octane is not allowed and will result in a disqualification with no exceptions (hard limit). This limit gives competitors a 99.99+% confidence level that fuel purchased from a pump marked 93 octane is compliant. Warning: Competitors attempting to approach the 95.9 octane limit through mixing or by any other means may inadvertently create fuel that appears compliant but may test above the 95.9 hard limit.

CLUB SPEC Mustang (CSM)

Eligible Vehicles

2005-2009 Ford Mustang GT (S197 Chassis)

Including California Special, Shelby GT*, and Bullitt* models

*Must use engine and rear gear ration listed below and either complete OE suspension or Performance Kit suspension

Vehicle Requirements

Engine: 4.6L, 3 Valve V8

Rear Axle Assembly Gear Ratio: 3.55:1

Required Performance Kit

A. Parts Specified below (tires, wheels, and suspension) must be used. All components and parts (e.g., hardware) are required to be installed per manufacturer instructions. Original equipment (OE) or equivalent components are not allowed.

B. Anti-roll (sway) bar end links may be substituted but may serve no other purpose.

C. Tires: Goodyear F1 Supercar 3 (220 Treadwear), size: 275/40R18

D. Wheels

- Diameter and width (in): 18x9.5
- Offset, including wheel spacer (mm): +35 (35ET or ET35) or greater

CSM

- c. Weight, without spacer if used, minimum (lbs.): 17, including:
 - i. Wheel Weights
 - ii. TPMS sensor if installed
 - iii. Tire valve stem (type unrestricted)
- d. Wheel spacers are allowed provided the resultant combination with the wheel complies with the offset requirements.

E. Suspension

- a. Sealed Koni Sport Strut, Front, Part# TBA
- b. Sealed Koni Sport Strut, Rear, Part# TBA
- c. Eibach Pro-Kit Lowering Springs- Part# 35101.140
- d. Choice of:
 - i. Strano Performace Parts kit Part# SpecS197-1. Includes bars, bushings, collar locks, Billet aluminum rear mounts
 - ii. Strano Performance Parts kit Part# SpecS197-2. Same as above, adding front sway bar mount reinforcements + Billet Front sway bar brackets
 - iii. Eibach Mustang Anti-Roll Bar Kit- Part# MM5CC-1
- e. Choice of
 - i. Maximum Motorsports Caster Camber Plates- Part# MM5CC1
 - ii. BBK Performance Caster Camber Plates- Part# 2551

Authorized Changes/Modifications

- A. Parts superseded by Ford® may be used.

Bodywork/Interior

- A. A commonly available short throw shifter may be utilized, examples include:

- a. Hurst Competition Plus Short Throw Shifter, Part# TR-3650
- b. STEEDA Ford Mustang Tri-Ax Shifter, Part# 555-7305

Safety

- A. Vehicles that do not meet SCCA Level 2 Safety may not substitute or modify seats or steering wheel, however driver restraints as outlined in Solo® Rules section 3.3.1, Driver Restraints, are allowed. Seats may not be cut to allow for the installation of alternate seat belts or harnesses. A horizontal "harness bar" may be used as part of the installation hardware for allowed driver restraints provided it has no more than two (2) attachment points to the chassis and is bolted at those locations. A C-type harness bar may also be used; it may have four (4) bolted attachment points to the chassis (2 primary and 2 supporting connections to resist rotation). Truss-type harness bars with more than two (2) attachment points are not allowed.

Brakes

- A. Ford Racing 2005-2014 Mustang GT 14-inch SVT Brake Upgrade Kit, Part# M-2300-S, or any Ford OEM kit utilizing 14" rotors and Brembo 4 piston calipers may be utilized.
- B. No Rear brake caliper relocation kits are allowed.
- C. Goodridge G-Stop Brake Line Kit is allowed, Part#12364 (these lines are included in the Ford Racing SVT Kit listed above)

CSM

D. The make and material of brake linings (pads) may be changed.

Suspension

A. A commonly available aftermarket Panhard Bar, that mounts in the OEM/ Stock body and axle locations may be utilized, including those adjustable for length. This does not allow for Panhard Bar relocation, adjustable height Panhard Bars, or replacement of the Panhard Bar Brace. Any bushing, rod-end, spherical bearing may be used. Examples include:

- a. UMI Performance On-Car Single Adjustable Panhard Bar,
Part#UPI-1044-B
- b. STEEDA Autosports Street Panhard Bar Kit 05-14 Mustang,
Part#555-2551-A
- c. Eibach Pro-Alignment Performance Kit Panhard Bar
Part#5.72045K

B. The UMI Ford Mustang GT Adjustable Front Strut Tower Brace may be utilized, Part# UMI-1005-B

C. The STEEDA Mustang Upper Third Link Spherical Differential Bearing may be utilized, Part# 555-4104

Engine and Drivetrain

A. The air intake system, upstream of the throttle body, may be replaced with a CARB approved, commonly available aftermarket unit that utilizes a cone filter and divider wall. Examples include:

- a. K&N Part# 57-2565
- b. Airaid Part# 450-172
- c. aFe Power Part# 51-10293
- d. aFe Power Part# 54-10293

B. The engine management system parameters and operation of internal combustion engines may be modified only via the methods listed below.

- a. OE ECU software may be reprogramed, but no changes to the factory ECU hardware are permitted.
- b. Any OE OBD2 or newer communications port functionality must remain.

D. Ford Performance Traction-Lok Rebuild Kit with Carbon Fiber Clutch Pack may be utilized, Ford Performance Part# M-4700-C.

E. The installation of oil catch tanks or oil separators is allowed provided the function of the PCV system remains functional.

F. An oil cooler is allowed provided no unauthorized modifications are made to perform the installation.

G. Mufflers may be substituted, provided there are two, one in each stock location no smaller than 6 inches in diameter or 4x6 inches height and width if oval.

H. Mufflers may be substituted, provided there are two, one in each stock location no smaller than 6 inches in diameter or 4x6 inches height and width if oval.

CLUB SPEC MX-5 (CSX)

Eligible Vehicles

CSM

2006-2015 Mazda MX-5 (NC Chassis)

Vehicle Requirements

6-Speed Manual Transmission or Automatic Transmission

Minimum Vehicle Weight, as weighed without Driver (lbs): 2500

Required Performance Kit

A. Parts specified below (tires, wheels, and suspension) must be used.

All components and parts (e.g., hardware) are required to be installed per manufacturer instructions. Original equipment (OE) or equivalent components are not allowed.

B. Tires: Falken Azenis RT660, size: 225/45R17

C. Wheels

- a. Diameter and width (in.): 17x8
- b. Offset, including wheel spacer (mm): +45 (45ET or ET45) or greater
- c. Weight, without spacer if used, minimum (lbs.): 15, including:
 - i. Wheel Weights
 - ii. TPMS sensor if installed
 - iii. Tire Valve stem (type unrestricted)
- d. Wheel spacers are allowed provided the resultant combination with the wheel complies with the offset requirements.

D. Suspension

- a. Penske Front Shock (2), Part# 0000-04-5291-SA
- b. Mazda Motorsport Front Mount Kit, Part# 0000-04-5359
- c. Mazda Motorsport Front Offset Bushing Kit, Part# 0000-04-5407-NC
- d. Eibach Front Spring (2), Part# 0000-04-9700-08
- e. Penske Rear Shock (2), Part# 0000-04-5292-SA
- f. Mazda Motorsport Rear Mount Kit, 0000-04-5358
- g. Mazda Motorsport Rear Shock Alignment Spacer, Part# 000004-5294
- h. Eibach Rear Spring (2), Part# 0000-04-9400-07
- i. Eibach Helper Springs (4), Part# 0000-04-9926
- j. Eibach Front and Rear Sway Bar Kit, Part# 0000-04-5306-EB
- k. Mazda Motorsport Sway Bar End Links (4), Part# 0000-04-5597-KT
- l. Penske Adjustment Knob (Recommended), Part# 0000-04-5293

Authorized Changes/Modifications

A. Parts superseded by Mazda® may be used.

Safety

A. Vehicles that do not meet SCCA Level 2 Safety may not substitute or modify seats or steering wheel, however a lap belt, as outlined in Solo® Rules section 3.3.1, Driver Restraints, is allowed. Seats may not be cut to allow for the installation of alternate seat belts or harnesses.

B. Level 2 Fire Suppression is not required for Solo Events

CSX Brakes

- A. The make and material of brake linings (pads) may be changed.
- B. Goodridge G-Stop Brake Line Kit is allowed, Part# 0000-03-5212
- C. Mazda Motorsports 2.5" Brake Duct Kit is allowed, Part# 0000-03-5301-NC

Suspension

- A. The Mazda Motorsports Competition Rear Hub, Part# 0000-04-5530, and Rear Hub Bearing, Part# 0000-04-5531 may be utilized.
- B. Mazda RX-8 Front Hub may be utilized, Part# F189-33-04X

Engine and Drivetrain

- A. The air intake system, upstream of the throttle body, may be replaced with the Mazda Motorsport Intake System, Part# 0000-06-5150-KT
- B. The installation of oil catch tanks or oil separators is allowed provided the function of the PCV system remains functional.
- C. An oil cooler is allowed provided no unauthorized modifications are made to perform the installation, Mazda Motorsports Oil Cooler Adaptor with Lines Part# 0000-015511-KT is recommended.
- D. Alternate exhaust and muffler may be utilized provided it mounts to the manifold flange labeled "Z" below, the muffler is in the stock location and is at least 6 inches in diameter or 4x6 inches if oval.

